



Terminal Services & Avimark Printer Setup



AVIMARK®

Terminal Services & Printer Setup

The Avimark Site feature will only work with (TCP/IP) network ready printers or (TCP/IP) network print servers. The only recommended print servers at this time are HP JetDirect en1700 for use with USB printers and HP JetDirect 170X or 300X for connecting parallel printers.

1. Start and log on to a local workstation.
2. Set up printers/print servers on local workstations per manufacturer's instructions. Please contact the manufacturer for assistance.
3. Test print from Windows to verify printer/print server operation.
4. Share printers. Note the share name and workstation name for later use.
5. Establish a VPN connection between the remote workstation and the Terminal Server. Please contact Microsoft or your local Network Technician for assistance.
6. From the local workstation, log in to Terminal Server with a workstation unique username.
7. Setup as a network printer, connect to this printer, \\remoteworkstationname\printer_sharename.

Test print from the Terminal Server to verify printer/print server operation.



Avimark does not provide support for the preceding steps. Please consult your local technician and/or Microsoft for assistance. If the Terminal Server cannot print a Windows test page to the remote site's printers, Avimark will not print.

1. Start Avimark from the Terminal Server desktop.
2. Set up printers in Avimark: **Utilities > Printer Setup.**
3. Test printers in Avimark.
4. Repeat the steps for each remote location workstation.